



KINTEK SOLUTION

## Vacuum Hot Press Furnance Catalog

Contact us for more catalogs of Sample Preparation, Thermal Equipment, Lab Consumables & Materials, Bio-Chem Equipment, etc...

# KINTEK SOLUTION

## COMPANY PROFILE

### >>> About Us

Kintek Solution Ltd is one technology orientated organization, team members are devoted to probing the most efficient and reliable technology and innovations in the scientific researching equipment, fields like biochemical reacting, new materials researching, heat treatment, vacuum creating, refrigerating, as well as pharmaceutical and petroleum extracting equipment.

In the past 20 years, we earned rich experiences in this researching equipment field, we are capable to supply both the equipment and solution according to customer's needs and realities, we have also developed lots of customer tailored equipment according to a specific working purpose, and we have lots of successful projects in many universities and institutes from different countries, like Asia, Europe, North and South America, Australia and New Zealand, Middle East, and Africa.

Profession, quick response, hard working, and sincerity is a remarkable label of our team members working attitude, which earn us a sound reputation among our clients.

We are here and ready to service our clients from different countries and regions, and share the most efficient and reliable technology together!



# Vacuum Hot Press Furnace

Item Number: KT-VHP



## Introduction

Discover the advantages of Vacuum Hot Press Furnace! Manufacture dense refractory metals & compounds, ceramics, and composites under high temp and pressure.

[Learn More](#)

Specification	<ul style="list-style-type: none"> <li>The electric furnace is heated by a vertical furnace body (pressure ranges from 5-800T, and the pressurization method is divided into one-way and two-way). The feeding and discharging methods are divided into top and side. , electronic control system and other components.</li> </ul>
Furnace shell	<ul style="list-style-type: none"> <li>The furnace shell is a double-layer water-cooled structure, the inner layer is strictly polished stainless steel, the outer layer is stainless steel sandblasting matte treatment or carbon steel anti-rust treatment, water cooling is passed between the double layers, and the furnace shell does not exceed 60 °C. The furnace cover is lifted by a mechanical mechanism, manually rotated backwards to open (one-way pressure), and a locking device is installed on the furnace cover.</li> </ul>
Stove side	<ul style="list-style-type: none"> <li>The side of the furnace is equipped with an observation window, a thermocouple automatic entry and exit mechanism, an infrared thermometer and a water-cooled electrode (three-phase). The automatic entry and exit of the thermoelectric cell is electric, with high and low temperature automatic switching. In order to prevent accidents caused by abnormal furnace temperature, there is also an over-temperature protection thermocouple on the side of the furnace.</li> </ul>
The heating element	<ul style="list-style-type: none"> <li>The heating element is made of graphite tube (or molybdenum wire), which can be divided into single-phase and three-phase heating. The rational design of the heating element improves the uniformity of the furnace temperature.</li> </ul>
The insulation layer	<ul style="list-style-type: none"> <li>The insulation layer is made of graphite (or graphite paper), carbon felt, etc., which has good insulation performance, and the unique structural design reduces the vacuuming time. The insulation layer of the molybdenum wire hot pressing furnace is a metal reflective screen.</li> </ul>
The vacuum system	<ul style="list-style-type: none"> <li>The vacuum system consists of two-stage vacuum pumps, one oil diffusion pump and one mechanical pump to complete the high and low vacuum. The vacuum valve adopts the high-vacuum baffle valve designed and produced by our company, which can realize automatic switching and control of high and low vacuum with digital display vacuum gauge and PLC.</li> </ul>
The main circuit of the electric control system	<ul style="list-style-type: none"> <li>The main circuit of the electric control system is low-voltage and high-current input. The electric control cabinet is made with reference to the standard cabinet of Rittal. It is humanized design. There are graphic simulation screens and buttons on the control panel. The operation is intuitive and convenient. The temperature and pressure control are controlled by imported brand programs. Instrument, the cabinet is equipped with a PLC, and the sintering process is automatically completed near the preset program. The control system has sound and light alarm functions for abnormal phenomena such as water cut-off, over-temperature, over-current, and thermocouple automatic switching failure.</li> </ul>
Working temperature	1500°C / 2200°C
Heating element	Molybdenum/Graphite
Working pressure	10-400T
Press distance	100-200mm
Vacuum pressure	6x10 <sup>-3</sup> Pa

Effective working  
area diameter  
range 90-600mm

Effective working  
area diameter  
range 120-600mm

# Vacuum Lamination Press

Item Number: KT-VLP



## Introduction

Experience clean and precise lamination with Vacuum Lamination Press. Perfect for wafer bonding, thin-film transformations, and LCP lamination. Order now!

[Learn More](#)

Dimensions	Over-all: 775mm(L) x 550mm(W) x 1325mm(H)		
Structure	<ul style="list-style-type: none"> <li>• Two 135 x 135 mm flat heating platens made of high temperature resistant Cr steel with max. working temperature of 500°C</li> <li>• 1000W Heating element is inserted into the center of the heating plates for fast heating</li> <li>• Max. Load on 135x135mm Heated Platen: 10 Metric Tons at 500°C ( 55 kg/cm<sup>2</sup> );20 Metric Tons at RT ( 110 kg/cm<sup>2</sup> )</li> <li>• Two precision temperature controllers which control two heating plates separately</li> <li>• with 30 programmable segments</li> <li>• Water cooling jackets are built on the both top &amp; bottom of the heating plates for assisting cooling</li> </ul>		
Hydraulic Pump	<ul style="list-style-type: none"> <li>• Modified electric hydraulic press is connected to vacuum chamber.</li> <li>• Movable distance between two heating plates: 15 mm.</li> <li>• Automatic max. pressure controlled via a digital pressure gauge.</li> <li>• Pressure accuracy: +/-0.01 Mpa ( 0.1 kg/cm<sup>2</sup> )</li> <li>• Two flat heating plates are installed with water cooling plates for Max. 500°C working temperature.</li> <li>• Water cooling (&gt;15L/min) is required to cool the heating plates when the operating temperature is over 200 °C.</li> </ul>		
Temperature control and Pressure Display	<ul style="list-style-type: none"> <li>• Two precision temperature controllers with 30 programmable segments control the heating plates .</li> <li>• separately with +/-1°C accuracy.</li> <li>• The temperature controllers have PID auto tune function, over-temperature protection and thermal couple broken protection.</li> <li>• Max. Temperature: 500°C with inert gas or vacuum with accuracy +/-1°C</li> <li>• Max. Heating rate: 2.5°C/min</li> <li>• Software and PC interface is built in the controller , which can be connected to a PC for computer controlling via a RS232 connector.</li> <li>• Digital pressure meter ( controller ) is built outside the vacuum chamber.</li> <li>• You can set pressure at the desired value which can stop the electric hydraulic press automatically.</li> </ul>		
Vacuum Chamber	<ul style="list-style-type: none"> <li>• Electric hydraulic press and heating plates are placed inside then vacuum chamber.</li> <li>• Vacuum chamber is made of SS304 with the size: 525Lx480Wx450H (mm).</li> <li>• Vacuum chamber Capacity : about 75 Liters.</li> <li>• 300mm dia. vacuum sealed hinged type door with 150mm Dia. quartz glass window is installed for easy sample loading and observation.</li> <li>• Silicone O-ring can be used for all vacuum sealings .</li> <li>• One precision digital vacuum guage ( 10E-4 torr ) is installed on the vacuum chamber .</li> </ul>		
Model	KT-VLP100	KT-VLP300	KT-VLP400
Heating plate size	100x100mm	300x300mm	400x400mm
Plates travel distance	30mm	40mm	40mm

Working pressure	30T during heating/40T in the cold state
Pressure gauge	Digital pressure gauge
Heating temperature	<500°C
Temperature control	Touch screen with PID thermal controller
Vacuum chamber	304 Stainless steel
Vacuum pump	Rotary vane vacuum pump
Vacuum pressure	-0.1Mpa
Power supply	AC110-220V, 50/60HZ

# Vacuum Tube Hot Press Furnace

Item Number: KT-VTP



## Introduction

Reduce forming pressure & shorten sintering time with Vacuum Tube Hot Press Furnace for high-density, fine-grain materials. Ideal for refractory metals.

[Learn More](#)

Hydraulic press	<p>Working pressure: 0-30Mpa            Travel distance: Pressure stability: <math>\leq 1\text{MPa}/10\text{min}</math>            Pressure meter: Digital pressure gauge            Drive solution: Electric drive with standby manual drive</p>
Vertical split furnace	<p>Working temperature: <math>\leq 1150^\circ\text{C}</math>            Heating element: Ni-Cr-Al resistance wire with dipped Mo            Heating speed: Hot zone length: 300mm            Constant temperature zone: 100mm            Controller: Touch screen with PID thermal controller            Rated power: 2200W</p>
Vacuum furnace tube	<p>Tube material: Quartz tube(Optional Alumina/Nickel alloy)            Tube diameter: 100mm(Optional 120/160mm)            Vacuum sealing: SS flange with silicon O ring            Flange cooling method: Inter layer water circulating cooling</p>
Graphite pressing die	<p>Die material: High purity graphite            (Graphite must work under vacuum to prevent oxidation)            Pressure rod diameter: 87mm            Sleeve die size: 55mm OD/ 50mm Height            Die inserts: OD22.8 x ID20.8            Pushing Rod: 12.7mmOD/40mm Height            Other sizes die can be customer made</p>
Vacuum pump setup	<p>Rotary vane pump vacuum is up to 10<sup>-2</sup> torr            Turbo pump station vacuum is up to 10<sup>-4</sup> torr</p>
Electric power supply	<p>AC110-220V, 50/60HZ</p>

# Spark Plasma Sintering Furnace Sps Furnace

Item Number: KTSP



## Introduction

Discover the benefits of Spark Plasma Sintering Furnaces for rapid, low-temperature material preparation. Uniform heating, low cost & eco-friendly.

[Learn More](#)

Configuration	<ul style="list-style-type: none"> <li>Stainless Steel Chamber - Suitable for Controlled Inert Gas or Vacuum Condition</li> <li>Sintering Press Unit</li> <li>Sintering DC Pulse Generator</li> <li>Vacuum Unit</li> <li>Sintering Control Unit</li> </ul>
Temperature controller	<ul style="list-style-type: none"> <li>Precision Eurotherm temperature controller is built in</li> <li>Overshooting temperature is less than 5°C at the fastest heating rate</li> <li>Temperature accuracy :</li> </ul>
Hydraulic Press	<ul style="list-style-type: none"> <li>Manual operated hydraulic press to apply pressure.</li> <li>Max pressure: 20 T</li> <li>Digital Pressure gauge is built in with over-pressure alarm.</li> </ul>
Vacuum Chamber	<ul style="list-style-type: none"> <li>Vertical vacuum Chamber</li> <li>Inner Double Layers Stainless Steel Reflectors</li> <li>Rotary Pump included</li> </ul>
Dimension	<ul style="list-style-type: none"> <li>Power Supply :760 L X 460 W X 1820 H, mm</li> <li>Furnace: 970 L X 720 W X 1400 H, mm</li> </ul>

Model	KTSP-10T-5	KTSP-20T-6	KTSP-20T-10	KTSP-50T-30
Rated power	50Kw	60Kw	100Kw	300Kw
Output current	0-5000A	0-6000A	0-10000A	0-30000A
Input voltage	0-10V	0-10V	0-10V	0-10V
Rated temperature	2300°C			
Rated pressure	100KN	200KN	200KN	500KN
Sample size	Ø30mm	Ø50mm	Ø100mm	Ø200mm
Ram stroke	100mm	100mm	100mm	200mm
Ultimate vacuum	1Pa			



# 600T Vacuum Induction Hot Press Furnace

Item Number: KT-VH



## Introduction

Discover the 600T Vacuum Induction Hot Press Furnace, designed for high-temperature sintering experiments in vacuum or protected atmospheres. Its precise temperature and pressure control, adjustable working pressure, and advanced safety features make it ideal for nonmetal materials, carbon composites, ceramics, and metal powders.

[Learn More](#)

Maximum pressure	600T
Mold outer diameter	Ø680mm
Mold material	Graphite
Large sample size	Ø500mm
Cold vacuum degree	10Pa
Furnace body form	One for two
Heating method	Induction
Pressure method	Four-column mechanical pressurization



## Kintek Solution

Head Quarter: No.89 Science Avenue, High-Tech Zone,  
Zhengzhou, China

Hongkong Office: 300 Lockhart Road, Wan Chai,  
Hongkong

Canada Office: Boulevard Graham, Mont-Royal, QC, H3P  
2C7, Canada

